

Building Science with CMake

Bill Hoffman bill.hoffman@kitware.com

Bill Hoffman

- One of 5 founders of Kitware Inc
- Originator of CMake build tool
- Ultra runner (barefoot/sandals)









Collaborative Software R&D

Algorithms & applications
Software process & infrastructure
Support & training
Open source leadership


Supporting all sectors

Industry, government & academia

Successful small business

Founded in 1998; privately owned Offices in NY, NC, NM & Lyon France





Discourse on the (Scientific) Method,

Descartes 1637

DOUBTING EVERYTHING, and only believe in those things that are evidently true (REPRODUCIBLE)



If it's not reproducible, it's not Science

Nullius in Verba



"take nobody's word for it" Royal Society 1640



"Software mather langua Seidel

SUVAT equations

```
In elementary physics the ab
    v = u + at [1]
    s = ut + \frac{1}{2}at^2
   s = \frac{1}{2}(u+v)t
  v^2 = u^2 + 2as
   s = vt - \frac{1}{2}at^2
```

where u has replaced vo, s re displacement), u = initial velo

Scen switch (m_symmetry[i]) { case S: ation

```
m_moIndices[i] = indexM0++;
 m_cIndices.push_back(static_cast<unsigned int>(m_qto(N.size()));
 // Normalization of the S-type orbitals (normalization used in JMol)
 // (8 * alpha^3 / pi^3)^0.25 * exp(-alpha * r^2)
 for(unsigned j = m_qtoIndices[i]; j < m_qtoIndices[i+1]; ++j) {</pre>
    m_gtoCN.push_back(m_gtoC[j] * pow(m_gtoA[j], 0.75) * 0.71270547);
 break:
case P:
 m_moIndices[i] = indexM0;
 indexM0 += 3;
 m_cIndices.push_back(static_cast<unsigned int>(m_qtoCN.size()));
 // Normalization of the P-type orbitals (normalization used in JMol)
 // (128 alpha^5 / pi^3)^0.25 * [xlylz]exp(-alpha * r^2)
 for(unsigned j = m_gtoIndices[i]; j < m_gtoIndices[i+1]; ++j) {</pre>
    m_gtoCN.push_back(m_gtoC[j] * pow(m_gtoA[j], 1.25) * 1.425410941);
    m_gtoCN.push_back(m_gtoCN.back());
    m_gtoCN.push_back(m_gtoCN.back());
 break;
case D:
 // Cartesian - 6 d components
 // Order in xx, yy, zz, xy, xz, yz
 m_moIndices[i] = indexM0;
 indexM0 += 6;
 m_cIndices.push_back(static_cast<unsigned int>(m_gtoCN.size()));
 // Normalization of the P-type orbitals (normalization used in JMol)
 // xx|yy|zz: (2048 alpha^7/9pi^3)^0.25 [xx|yy|zz]exp(-alpha r^2)
 // xy|xz|yz: (2048 alpha^7/pi^3)^0.25 [xy|xz|yz]exp(-alpha r^2)
 for(unsigned j = m_gtoIndices[i]; j < m_gtoIndices[i+1]; ++j) {</pre>
    m_gtoCN.push_back(m_gtoC[j] * pow(m_gtoA[j], 1.75) * 1.645922781);
    m_gtoCN.push_back(m_gtoCN.back());
    m_gtoCN.push_back(m_gtoCN.back());
```

[12.]

OMATA SIVE SMOTUS

Lex. L.

in statu suo quiescende vel movende uniforquatenus a viribus impressis cogfine statues

nt in motibus fuis nifi quatenus a refiftenur & vi gravitatis impelluntur deorium. artes cohærendo perpetuo retrahunt fese on ceffat rotari nili quatentis ab aere ren Planetarum & Cometarum corpora mok circulares in spatiis minus resistentibus

Lex. II.

ionalem effe vi morrer impresta, & fieri fee restam qua vis illa imprimitur.

etnvis generet, dupla duplum, tripla trirul & femel, five gradatim & fucceffive imsotus quenism in eandem femper plagam minatur, fi corpusantea movebatur, molditur, vel contrario fubducitur, vel oblicum co secundum utriuses determinatio-Lex. Ili-



Failure of Reproducibility


- Nature (March 2012)
 - Glenn Begley, former head of cancer research at pharma giant Amgen
 - Lee M. Ellis, cancer researcher at the University of Texas

Found that more than 90% of papers published in science journals describing "landmark" breakthroughs in preclinical cancer research, are not reproducible, and are thus just plain wrong.




CMake came from open science

- NIH Visible Human Project
 - Data, CT/MR/Slice 1994/1995
 - Code (ITK) 1999
 - CMake Cross platform build tool







How CMake Changes The Way We Build C++

- Boost aims to give C++ a set of useful libraries like Java, Python, and C#
- CMake aims to give C++ compile portability like the compile once and run everywhere of Java, Python, and C#
 - Same build tool and files for all platforms
 - Easy to mix both large and small libraries















CMake most popular Kitware Tool

KDE 2006 – Tipping Point!






- Google Search Trends and ohloh comparisons with auto*
- 5000+ downloads per day from www.cmake.org
- Major Linux distributions and Cygwin provide CMake packages
- KDE, Second Life, CLang, many others


CMake is the most popular build tool at 38%.

 2014 study data by JetBrains in the development of a new C++ IDE, that is CLion found CMake to have the highest adoption by the 4.4 million worldwide C++ developer community






Science is not done by one person and problems bigger





Multiscale Design



Robot Operating System (ROS) **Statistics**


Metrics as of July 2015 (http://wiki.ros.org/Metrics):

- Unique IPs downloading ROS debs: ~45,000/month
- Academic papers citing original paper: 1843
- Robot models officially supported: >101
- wiki.ros.org pageviews: ~37,000/day



Longest distance a ROS robot has traveled from Earth: 270 miles

itware



ROS is BIG

- Almost 2000 packages in our Indigo release: http://www.ros.org/debbuild/indigo.html
- All of those packages, as far as I know, are CMake projects or at least wrapped in CMake.
- They are contributed by roughly 370 different people/groups, based on the contributors to our releases repo: https://github.com/ros/rosdistro
- CMake makes up ~6% (>12kLoC) of the ROS Indigo code base (for desktop-full which is a subset and what we consider the core).



2000 CMake based packages in ROS

::: ROS.org

ROS Indigo Build Status

wet - catkin

dry - rosbuild

1 2 3

- 1. building repo
- 2. shadow-fixed repo
- 3. ros/public repo

same version

different version

missing

obsolete

intentionally missing

Quick: all, sync, regression, diff, blue, red, yellow, gray

showing 1986 of 1986 total

Name	Repo	Version	Wet Status	Maintainer	IsrcS IbinS32 1981,981,926 1901,901,862	
abb	abb	1.2.0-0	wet developed	Shaun Edwards		
abb_driver	abb	1.2.0-0	wet developed	Shaun Edwards		
abb_irb2400_moveit_config	abb	1.2.0-0	wet developed	Shaun Edwards (Southwe.		
abb_irb2400_moveit_plugins	abb	1.2.0-0	wet developed	Shaun Edwards (Southwe.		
abb_irb2400_support	abb	1.2.0-0	wet developed	Shaun Edwards (Southwe.		
abb_irb5400_support	abb	1.2.0-0	wet developed	Shaun Edwards (Southwe.		
abb_irb6600_support	abb	1.2.0-0	wet developed	Shaun Edwards (Southwe.		
abb_irb6640_moveit_config	abb	1.2.0-0	wet developed	Shaun Edwards (Southwe.		
acado	acado	1.2.1-5	wet maintained	Mike Purvis		
access_point_control	linux_networking	1.0.11-0	wet maintained	Devon Ash		
25.5555.55	20.000					
zeroconf_jmdns_suite	zeroconf_j	mdns_suite	0.2.1-0 wet n	naintained Daniel Stonier		
zeroconf msgs	zeroconf r	nsas	0.2.1-0 wet d	leveloped Daniel Stonier		



Why CMake? It's easy, and works well

 A build system that just works

 A build system that is easy to use cross platform

Typical Project without CMake (curl)

```
$ Is
CHANGES
                 RELEASE-NOTES curl-config.in missing
CMake
               acinclude.m4 curl-style.el mkinstalldirs
CMakeLists.txt
                  aclocal.m4 depcomp
                                            notes
build
         docs
                    notes~
COPYING
                buildconf
                            include
                                        packages
CVS
              buildconf.bat install-sh
                                      reconf
ChangeLog
                 compile
                             lib
                                     sample.emacs
Makefile
               config.guess libcurl.pc.in src
                 config.sub Itmain.sh
Makefile.am
                                         tests
Makefile.in
                configure m4
                                      vc6curl.dsw
RFADMF
                configure.ac maketgz
```

\$ Is src/

```
CMakeLists.txt Makefile.riscos curlsrc.dsp hugehelp.h
                                                      version.h
           Makefile.vc6 curlsrc.dsw macos
                                                writeenv.c
Makefile.Watcom Makefile.vc8 curlutil.c main.c
                                                    writeenv.h
              config-amigaos.h curlutil.h makefile.amiga writeout.c
Makefile.am
Makefile.b32 config-mac.h getpass.c makefile.dj
                                                    writeout.h
             config-riscos.h getpass.h mkhelp.pl
Makefile.in
             config-win32.h homedir.c setup.h
Makefile.inc
Makefile.m32
               config.h.in
                            homedir.h urlglob.c
                            hugehelp.c urlglob.h
Makefile.netware curl.rc
```



Why CMake? It's fast

http://blog.qgis.org/?q=node/16 : "I was quite surprised with the speed of building Quantum GIS codebase in comparison to Autotools."

	Task	CMake			Autotools			
	Configure	0:08			Automake: 0:41 Configure: 0:20			
	Make	12:15		21.16				
	Install	0:20	 + (t i sec) +	HDD	+	SSI		
	IIIStaii	0.20	 	autohell	cmake	autohell	cmake ++	
	Total	12:43	configuration 	7.015 10.399	2.592	5.613 7.804	1.589	
htt **Kitware**				17.414	2.592	13.417	1.589	
		tp://taskwarrior.org/proj	.mg1632	922.756	29.790	68.732	17.462	
		vs	Total	110.170	32.382	82.149	19.051	

CMake: Features

- Open-source cross-platform build manager using native tools
 - Visual Studio 6, 7.1, 2005, 2008, 2010, 2012, 2013, 2014
 - Borland make, Nmake, Unix make, MSYS make, MinGW make
 - Ninja
 - Xcode
- IDE Support
 - Code::Blocks
 - CodeLite
 - Eclipse
 - KDevelop
 - Kate
 - Sublime Text



CMake: Features (cont.)

- OSes: HPUX, IRIX, Linux, Mac OSX, QNX, SunOS, Windows, others
- Platform inspection commands can
 - Search for
 - Programs
 - Libraries and Header files
 - Packages
 - Determine hardware specifics like byte order
- Compiler Feature Detection (CMake 3.1)
 - target_compile_features



Why CMake? Quickly adapt to new technologies

- New build IDE's and compilers
 - Visual Studio releases supported weeks after beta comes out
 - Xcode releases supported weeks after beta comes out
 - ninja (command line build tool from Google) support contributed to CMake as ninja matured
- New compiler support
 - clang
 - gcc versions



CMake: Features (cont.)

- Support for complex custom commands
 - Cuda support
 - Qt's moc
- Optional component support
- Shared library building (versions for .so supported)
- Create configured .h files
- Single input format for all platforms
- Automatic dependency generation (C, C++, Fortran)
 - Full dependencies: build a target in some directory, and everything this target depends on will be up to date
- Parallel builds
- Out of source builds



CMake: Features (cont.)

- Color and progress output for make
- Automatically rerun cmake if any cmake input files change (works with Visual Studio using ide macros)
- Graphviz output for visualizing dependency trees
- Full cross platform install() system


```
~/My Builds/CMake-build26
   98%] Generating ../Docs/cmake.txt
  [100%] Built target documentation
   offman@CORRIN ~/My Builds/CMake-build26
  $ make -j3 cmake
    6%] [ 7%] [ 7%] Built target cmexpat
  Built target cmsysEncodeExecutable
  Built target cmzlib
    7%] [ 17%] Built target cmsysProcessFwd9x
   18%] Built target cmcompress
  [ 26%] Built target cmsvs
   53%] Built target cmcurl
   canning dependencies of target CMakeLib
   54%] Building CXX object Source/CMakeFiles/CMakeL
  cmVisualStudio10TargetGenerator.cxx
  [100%] Built target CMakeLib
  [100%] Built target cmake
   offman@CORRIN ~/My Builds/CMake-build26
```




CMake Documentation

- Mastering CMake Book
- Web Page: www.cmake.org
- http://www.cmake.org/Wiki/CMake
- mailing list: cmake@cmake.org
 - Full reference documentation
 - http://www.cmake.org/cmake/help/documentation.html
- Ships HTML, man, and command line help
 - Tutorial included and tested in source tree (Tests/Tutorial/)
 - reStructuredText and Sphinx
 - configured files
 - optional build components
 - install rules, test properties
 - system introspection





Cache Editors: cmake-gui (qt), ccmake (curses)



	BUILD_DOXYGEN BUILD_TESTING CMAKE_CONFIGURE_INSTALL_PREFIX CMAKE_CXX_FLAGS CMAKE_C_FLAGS CMAKE_INSTALL_PREFIX CURSES_EXTRA_LIBRARY CURSES_INCLUDE_PATH CURSES_LIBRARY DART_ROOT EXECUTABLE_OUTPUT_PATH FORM_LIBRARY LIBRARY_OUTPUT_PATH	Page 1 of 1 OFF ON /usr/local /usr/local NOTFOUND /usr/include /usr/lib/libcurses.a /cygdrive/c/hoffman/Dart /cygdrive/c/hoffman/CMake-gcc/ /usr/lib/libform.a
	BUILD_DOXYGEN: Build source docum	mentation using doxygen CMake Uersion 1.3 - developmen
	Press [enter] to edit option Press [c] to configure Press	[q] to generate and exit
		[q] to quit without generating
ı	Press [t] to topole advanced mode	(Currently Off)



Running CMake From The Command Line

 Useful for scripted builds or for projects with no options or with options correctly set by default on the first configure

```
#CC=gcc; CXX=g++
#CFLAGS, CXXFLAGS
cd MyProjectSourceDir
mkdir ../MyProjectSourceDir-build
cd ../MyProjectSourceDir-build
cmake ../MyProjectSourceDir
(cmake -Dvar=value)
```



CMake Scripts

- cmake –E command
 - Cross platform command line utility
 - Ex. Copy file, Remove file, Compare and conditionally copy, time etc
- cmake –P script.cmake
 - Cross platform scripting utility
 - Does not generate cmake_cache
 - Ignores commands specific to generating build environment



Creating Packages

Package config files come with installation

```
# myproj-config.cmake
include(${DIR}/myproj-targets.cmake)
set(myproj_INCLUDE_DIRECTORIES
   ${PREFIX}/include/myproj)

# myproj-config-version.cmake
set(PACKAGE_VERSION 1.3)
if("${PACKAGE_FIND_VERSION_MAJOR}" EQUAL 1)
   set(PACKAGE_VERSION_COMPATIBLE 1)
endif()
```

See "CMakePackageConfigHelpers" module for helper API



Qt5 Ships with CMake config files

```
cmake_minimum_required(VERSION 2.8.11)
project(testproject)
# Find includes in corresponding build directories
set(CMAKE_INCLUDE_CURRENT_DIR ON)
# Instruct CMake to run moc automatically when needed.
set(CMAKE_AUTOMOC ON)
# Find the QtWidgets library
find_package(Qt5Widgets)
# Tell CMake to create the helloworld executable
add_executable(helloworld WIN32 main.cpp)
# Use the Widgets module from Qt 5.
target_link_libraries(helloworld Qt5::Widgets)
```



Usage Requirements – target centric view not directory centric

Propagate

- Include Directories
- Compile Definitions
- Compile Options
- And More!



target_link_libraries and target_include_directories

target_link_libraries - Lets talk different linking types

- PUBLIC
- PRIVATE
- INTERFACE

Target_include_directories - Bring include directories when linking

target_include_directories(Foo INTERFACE \${zlib_dir})

 Anything that links to Foo will automatically have the zlib_dir on the include line



target_compile_options and target_compile_definitions

target_compile_options(Foo PRIVATE
 -fno-unused-parameter)

Silence really chatty libraries that you can't modify.

 Foo will have NDEBUG defined and anything that links to it will have that definition



Compiler Feature Detection

```
add_executable(new-app main.cxx)
  target_compile_features(new-app
    cxx_member_templates
    cxx_constexpr
    cxx_generic_lambda
write_compiler_feature_header(
   FILE "mycompiler_detection.h"
   PREFIX MyPrefix
   FEATURES
   cxx_static_assert
   cxx final
   cxx_variadic_templates
```





ExternalProject_add

- Module introduced in CMake 2.8
 - Allows the download, configure, build and install of software via custom commands
- Kitware Source Article: October 2009
 - http://www.kitware.com/products/html/BuildingExterna IProjectsWithCMake2.8.html
- Funded by Army Research Lab (ARL) –
 Computational Science Environment (CSE)



Titan Example











Test Data
Management
ExternalData

Distributed Version Control

- Meant for source code, not data
- Local history of source is good
 - Often modified → interesting history
 - Line-wise commits → good deltas
 - Fast log, blame, etc.
- Local history of data is bad
 - Rarely modified → boring history
 - Whole-file commits → poor deltas
 - No blame for binary files









Separating Data from Source

- Source must reference data
- Tests need matching data
- Links must be unambiguous
- Links must be lightweight
- Answer: content hash



Content-Addressed Storage

- Arbitrary locations
 - Local machine
 - Private server
 - Internet server



- Content verified by hash
- No need to trust provider if hash is strong



ExternalData Module - Source

- Start with real data file in source tree (locally)
- Source code references data by original file name

- Test works with real data file out of the box
- Then replace data file by a "content link"

```
$ cat ../Data/BrainWeb/brainweb1e1a10f20.mha.md5
0b2135e2035e5bd84d82f4929e68fbdc
```

- Conversion to content link can be scripted
- Data go to local or remote content-addressed storage



ExternalData Module - Build

- Build system handles creation of local instance
- Fetches data from arbitrary content-addressed storage

```
$ make ITKData
Generating ExternalData/Examples/Data/BrainWeb/brainweb1e1a10f20.mha
-- Fetching "http://.../MD5/0b2135e2035e5bd84d82f4929e68fbdc"
-- [download 100% complete]
-- Downloaded object: "ExternalData/Objects/MD5/0b2135e2035e5bd84d82f4929e68fbdc"
```

- Test uses local instance by original file name
 - \$ bin/SegmentationExamples9 CellularSegmentation2Test \
 ExternalData/Examples/Data/BrainWeb/brainweb1e1a10f20.mha ...
- Original file name provided by symbolic link if possible
 - \$ readlink ExternalData/Examples/Data/BrainWeb/brainweb1e1a10f20.mha
 ../../Objects/MD5/0b2135e2035e5bd84d82f4929e68fbdc



ExternalData Module - Fetch

- Method is a black box

 - Can change in future without breaking old versions
- Configured list of URL templates
 - file:///local/%(algo)/%(hash)
 - http://server.local/%(algo)/%(hash)
 - http://midas.kitware.com/...?algorithm=%(algo)&hash=%(hash)
- Try each location in order
 - Substitute for %(algo) and %(hash) in URL
 - Download and check content hash
- Kitwadene if hash matches, else continue

Coming to CMake

- Android.mk generation for CMake built libraries
- Integrated Android platform support simplifying tool chain file



Simple Qt Example

```
cmake minimum required(VERSION 2.8)
project(helloQt)
# find required dependencies
find package(Qt4 REQUIRED)
# create the executable
add executable(helloQt WIN32 MACOSX BUNDLE myqt.cxx)
target_link_libraries(helloQt ${QT_QTMAIN_LIBRARY} ${QT_LIBRARIES})
# installation and packaging
install(TARGETS helloQt DESTINATION bin)
include (InstallRequiredSystemLibraries)
set (CPACK PACKAGE VERSION MAJOR "1")
set (CPACK PACKAGE VERSION MINOR "0")
set(CPACK PACKAGE EXECUTABLES "helloQt" "Hello Qt")
include (CPack)
```





Simple Qt Example with Boost

```
cmake minimum required(VERSION 2.8)
project(helloQt)
# find required dependencies
find_package(Qt4 REQUIRED)
include(${QT_USE_FILE})
set(Boost_USE_STATIC_LIBS ON)
find_package(Boost REQUIRED signals)
include_directories(${Boost_INCLUDE_DIRS})
# create the executable
add_executable(helloQt WIN32 MACOSX_BUNDLE myqt.cxx ) target_link_libraries(helloQt ${QT_QTMAIN_LIBRARY} ${QT_LIBRARIES}
 ${Boost LIBRARIES} )
# installation and packaging
install(TARGETS helloQt DESTINATION bin)
include (InstallRequiredSystemLibraries)
set (CPACK_PACKAGE_VERSION_MAJOR "1")
set (CPACK_PACKAGE_VERSION_MINOR "0")
set(CPACK_PACKAGE_EXECUTABLES "helloQt" "Hello Qt")
include (CPack)
```




Automatic Testing Benefits









CDash Dashboard www.cdash.org



Six Sigma and Quality Research Software (GE Research)



Six Sigma and Quality Research Software





CDash can be used with other tools

- Jenkins Project Tango and others
- Buildbot
 - Extended buildbot to run the configure, build, and test steps for CMakebased projects with support for uploading build artifacts (packages, logs, etc.)
 - Buildbot parses the output of CTest to determine error and warning status
- Travis
- CircleCI
- Simple ctest cronjobs



CDash github/gitlab integration

- Buildbot is used to act on actions based on GitLab comments to trigger builds
- Builds may be constrained to specific builders or machines for targeted testing
- Buildbot reports back to merge requests once all the relevant builders have completed with links to buildbot itself



Testing with CMake

- include(CTest) or enable_testing() enables the ADD_TEST commands in a project
- add_test (testname exename arg1 arg2)
 - Executable should return 0 for a test that passes
- ctest an executable that is distributed with cmake that can run tests in a project.
- CDash testing Create web based dashboards to show the results of tests for each day



Video of ParaView Nightly Testing

```
MSYS
2.58 sec
0.26 sec
2.78 sec
1.04 sec
0.30 sec
1.12 sec
0.40 sec
  87% tests passed, 13 tests failed out of 101
    Total Test time (real) = 87.27 sec
The following tests FAILED:

55 - pgClientFlow2-Builtin (Failed)

87 - pgClientFlow2-Builtin (Failed)

88 - pgClientUndoRedo6-Builtin (Failed)

88 - pgClientUndoRedo6-Builtin (Failed)

78 - pgClientSPrineseries-Builtin (Failed)

68 - pgClientSPrineseries-Builtin (Failed)

72 - pgClientSaveHninationGeometry-Builtin (Failed)

65 - pgClientFlox3DReader-Builtin (Failed)

51 - pgClientFlox3DReader-Builtin (Failed)

44 - pgClientExtractBlock-Builtin (Failed)


45 - pgClientExtractBlock-Builtin (Failed)

76 - pgClientSpClientFloxBlock-Builtin (Failed)

Frors while running Clest
     C:\Kitware\ParaView3\bin>
                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            🖮 👺 🔑 5:48 PM
```



Trilinos (Multi-Package Dashboard) http://trilinos-dev.sandia.gov/cdash/index.php





Coverage Display GCov/Bullseye

_/Source/CTest/cmCTestUpdateHandler.cxx	68.21%	45	1
/Source/cmMakefileLibraryTargetGenerator.cxx	68.48%	60	2
//Source/cmTargetLinkLibrariesCommand.cxx	69.17%	17	1
/Source/cmGetPropertyCommand.cxx	69.31%	36	2
/Source/cmExportInstallFileGenerator.cxx	69.32%	16	2
_/Source/kwsys/ProcessUNIX.c	69.33%	371	11
./Source/cmVariableWatch.cxx	69.44%	8	1
<u>//Source/cmSystemTools.h</u>	69.64%	1	5
_/Source/cmComputeLinkDepends.cxx	69.89%	78	5
_/Source/CTest/cmCTestStartCommand.cxx	70.00%	12	0
./Source/cmMakefileExecutableTargetGenerator.cxx	70.83%	16	1
_/Source/cmLinkLibrariesCommand.cxx	70.83%	7	0
./Source/cmMakeDepend.cxx	71.01%	44	1
/Source/CTest/cmCTestBuildCommand.cxx	71.74%	26	0
_/Source/cmsys/auto_ptr.hxx	71.88%	1	1
_/Source/kwsys/testCommandLineArguments.cxx	71.88%	7	1
_/Source/CTest/cmCTestSVN.cxx	72.07%	57	2
_/Source/cmScriptGenerator.cxx	72.34%	20	1

```
Copyright (c) 2002 Kitware, Inc., Insight Consortium. All rights reserved.
               This software is distributed WITHOUT ANY WARRANTY; without even
               the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
               PURPOSE. See the above copyright notices for more information.
          #include "cmDefinePropertyCommand.h"
          #include "cmake.h"
          bool cmDefinePropertyCommand
          ::InitialPass(std::vector<std::string> const& args, cmExecutionStatus &)
00000013
            if(args.size() < 1)
              this->SetError("called with incorrect number of arguments");
            // Get the scope in which to define the property.
             cmProperty::ScopeType scope;
00000013
            if(args[0] == "GLOBAL")
              scope = cmProperty::GLOBAL;
00000003
            else if(args[0] == "DIRECTORY")
              scope = cmProperty::DIRECTORY;
00000003
            else if(args[0] == "TARGET")
00000003
```

```
Coverage produced by bullseye covbr tool:
     www.bullseye.com/help/ref_covbr.html
   * An arrow --> indicates incomplete coverage.
   * An X indicates a function that was invoked, a switch label that
      was exercised, a try-block that finished, or an exception handler
     that was invoked.
   * A T or F indicates a boolean decision that evaluated true or false.
     respectively.
   * A t or f indicates a boolean condition within a decision if the
     condition evaluated true or false, respectively.
   * A k indicates a constant decision or condition.
     The slash / means this probe is excluded from summary results.
        20 #include "cmLocalGenerator.h"
        21 #include "cmGlobalGenerator.h"
            bool cmCTestStartCommand
            ::InitialPass(std::vector<std::string> const& args, cmExecutionSta
-->F
              if (args.size() < 1)
                this->SetError("called with incorrect number of arguments");
        29
                return false;
              this->CTest->SetSpecificTrack(0):
              if ( cnt < args.size() -1 )
                if ( args[cnt] == "TRACK" )
        43
        44
                  this->CTest->SetSpecificTrack(args[cnt].c_str());
```



Valgrind / Purify

Site Name: dash17.kitware											
uild Name: Linux-g++4.0											
Name	Status	Memory Leak	Uninitialized Memory Read	Potential Memory Leak	Uninitialized Memory Conditional	Mismatched Deallocate	Freeing Invalid Memory	Invalid Pointer Read	Invalid Pointer Write	Labels	
tChart-TestBarSeriesColors	Passed		1	25							
tChart-TestChartWidget	Passed		1	26							
lace	Passed			2							
estHyperOctreeContourFilter	Passed			2	1						
estUncertaintyTubeFilter	Passed			2							
<u>estMultiBlock</u>	Passed			2	Dynamia analysis st		02.27.47				
emporalStatistics	Passed			3	Dynamic analysis st	arted on 2009-05-04	03:37:17				
<u>estGenericCutter</u>	Passed			2	Site Name: dash17.k	itware					
estActorLightingFlag	Passed			2	Build Name: Linux-g+-	+4.0					
<u>estLabelPlacer</u>	Passed			2	<u>TestMultiBlock</u> Passed						
<u>estOpacity</u>	Passed			2	==3002== Memcheck						
estTextActor3DAlphaBlending	Passed			2	==3002== Copyrigh: ==3002== Using Lil						
<u>TestAreaSelections</u>	Passed			2	==3002== Copyrigh					oron.	
estTranslucentImageActorDepthPeeling	Passed		2	2	==3002== Using va						
estGenericVertexAttributesGLSLDepthPeelingF	Pass Passed			2	==3002== Copyrigh ==3002== For more			, by Julian	Seward et	aı.	
Find: asio		t all Mate	th case	- 7	==3002==	•					
Tild. Usio	ous 🔊 riigriiigrii	i dii 🗀 Mata	in case		==3002== ==3002== ERROR SUI	MARY: O errors f	rom 0 context	s (sunnress	ed: 119 fr	nm 2)	
					==3002== malloc/f:	ree: in use at ex	it: 30,294 by	tes in 327	blocks.		
					==3002== malloc/f: ==3002== For coun				86 bytes a	llocated.	
					==3002== searching						
					==3002== checked :	2,298,764 bytes.					
					==3002== ==3002== 64 byte:	s in 1 blocks are	still reacha	ble in loss	record 15	of 34	
					==3002== at 0x	401DC87: realloc	(vg_replace_m	alloc.c:306)		
						52F83E5: (within 52F908E: (within					
						62F95F0: XrmGetSt				0.6.2.0)	
						659FB22: (within					
						55A0ED4: _XtDispl 5596DC7: XtOpenDi				.6.0.0)	
					==3002== by 0x	437DD13: vtkXRend	erWindowInter	actor::Init	ialize() (/indowInteractor.cx
						42EFDD0: vtkRende 441E401: vtkXOpen					do: avv.1946)
						141E401: vtkXOpen 8081AB6: TestMult					.uow.cxx:1846)
					==3002== by 0x	805B2E8: main (Gr				-,	
					==3002==						



CDash Email Notification

A submission to CDash for the project CMake has failing tests. You have been identified as one of the authors who have checked in changes that are part of this submission or you are listed in the default contact list.

Details on the submission can be found at http://www.cdash.org/CDash/buildSummary.php?buildid=322849

Project: CMake

Site: destiny.kitware

Build Name: HP-UX-aCC

Build Time: 2009-04-29T14:28:00 EDT

Type: Continuous Tests failing: 85

Tests failing (first 5)

SystemInformationNew (http://www.cdash.org/CDash/testDetails.php?test=21959894&build=322849)

FindPackageTest (http://www.cdash.org/CDash/testDetails.php?test=21959898&build=322849)

FindModulesExecuteAll (http://www.cdash.org/CDash/testDetails.php?test=21959898&build=322849)

StringFileTest (http://www.cdash.org/CDash/testDetails.php?test=21959900&build=322849)

-CDash on www.cdash.org



CTest Command Wrappers Output

Build Time:2009-05-04T01:53:37 MDT

Found 1 Warnings

Errors are here.

Warı	Warning while building C++ object file "CMakeFiles/Kokkos_BaseSparseSolve.dir/cxx_main.cpp.o" in target Kokkos_BaseSparseSolve.						
Source File	packages/kokkos/test/BaseSparseSolve/cxx_main.cpp						
Label	Kokkos						
Command	"/Users/bmpersc/bin/gcc-4.3.3/bin/g++""-mmacosx-version-min=10.5""-ansi""-pedantic""-Wall""-Wno-long-long""-Wwrite-strings" "-g""-O0""-D_GLIBCXX_DEBUG""-I/Users/bmpersc/nightly/Trilinos.base/SERIAL_DEBUG/BUILD/packages/kokkos/src" "-I/Users/bmpersc/nightly/Trilinos.base/SERIAL_DEBUG/Trilinos/packages/kokkos/src" "-I/Users/bmpersc/nightly/Trilinos.base/SERIAL_DEBUG/Trilinos/packages/kokkos/test/BaseSparseSolve//BaseSparseMultiply" "-o""CMakeFiles/Kokkos_BaseSparseSolve.dir/cxx_main.cpp.o""-c" "/Users/bmpersc/nightly/Trilinos.base/SERIAL_DEBUG/Trilinos/packages/kokkos/test/BaseSparseSolve/cxx_main.cpp"						
Directory	/Users/bmpersc/nightly/Trilinos.base/SERIAL_DEBUG/BUILD/packages/kokkos/test/BaseSparseSolve						
Exit Condition	0						
Standard Output							
Standard Error	/Users/bmpersc/nightly/Trilinos.base/SERIAL_DEBUG/Trilinos/packages/kokkos/src/Kokkos_BaseSparseSolve.hpp: In member functio /Users/bmpersc/nightly/Trilinos.base/SERIAL_DEBUG/Trilinos/packages/kokkos/test/BaseSparseSolve.cxx_main.cpp:262: instanti /Users/bmpersc/nightly/Trilinos.base/SERIAL_DEBUG/Trilinos/packages/kokkos/src/Kokkos_BaseSparseSolve.hpp:646: warning: sugg /Users/bmpersc/nightly/Trilinos.base/SERIAL_DEBUG/Trilinos/packages/kokkos/src/Kokkos_BaseSparseSolve.hpp:693: warning: sugg /Users/bmpersc/nightly/Trilinos.base/SERIAL_DEBUG/Trilinos/packages/kokkos/src/Kokkos_BaseSparseSolve.hpp: In member functio /Users/bmpersc/nightly/Trilinos.base/SERIAL_DEBUG/Trilinos/packages/kokkos/test/BaseSparseSolve/cxx_main.cpp:287: instanti /Users/bmpersc/nightly/Trilinos.base/SERIAL_DEBUG/Trilinos/packages/kokkos/src/Kokkos_BaseSparseSolve.hpp:541: warning: sugg /Users/bmpersc/nightly/Trilinos.base/SERIAL_DEBUG/Trilinos/packages/kokkos/src/Kokkos_BaseSparseSolve.hpp:583: warning: sugg						








Query Filters: customize views

60 files changed by 2 authors as of Thursday, August 28 2014 - 21:00 EDT





New clang based tool support

Site	Build Name	Checker	Defect Count
localhost	ThreadSanitizer	ThreadSanitizer	1

Site Name: localhost

Build Name: ThreadSanitizer

Name Status data race Labels

simple_race Failed 1

Site	Build Name	Checker	Defect Count	
localhost	AddressSanitizer	AddressSanitizer	1	

Site Name: localhost

Build Name: AddressSanitizer

Name Status heap-use-after-free Labels

use-after-free Failed

Site	Build Name	Checker	Defect Count
localhost	MemorySanitizer	MemorySanitizer	1



Clang tools cont

- iwyu (include what you use)
- Scanbuild



Software Process – Reproducible


Results

Build, Test & Package



What is CPack

- CPack is bundled with CMake
- Creates professional platform specific installers



CPack Features

- Supports CMake-based and non-CMake-based projects
- Unix
 - TGZ and self-extracting TGZ (STGZ)
- Windows
 - NullSoft Scriptable Install System (NSIS / NSIS64)
 - WiX
- Mac OSX
 - DragNDrop
 - PackageMaker
- Deb
 - Debian packages
- RPM
 - RPM package manager




Using CPack


- On Windows install command line ZIP program, NSIS and WiX
- Setup your project to work with cpack
 - Get make install to work
 - install()
 - make sure you executables work with relative paths and can work from any directory
 - Set cpack option variables if needed
 - include(CPack)



CPack Components

http://www.cmake.org/Wiki/CMake:Component_Install_With_CPack








Examples of CMake Building Science



In The Beginning There Was VTK



Google Project Tango

Project Tango technology gives a mobile device the ability to navigate the physical world similar to how we do as humans. Project Tango brings a new kind of spatial perception to the Android device platform by adding advanced computer vision, image processing, and special vision sensors.

Core Technologies




Motion Tracking




Area Learning



Depth Perception









Project Tango: community effort

A truly open project

Project Tango is the result of technology partners and the developer community working hand in-hand to build something open and impactful.




















































































SubProject Dependencies
Graph for Google Tango from
CDash













Ground Truth Performance Report


0a25b9a / 2014Mar03_224231-d01f1dd4



















My CDash All Dashboards Log Out

Wednesday, October 07 2015 19:02:14 UTC

Dashboard Calendar Previous Current Project Settings

Sparse Mapping Plots

No file changed as of Wednesday, October 07 2015 - 08:00 UTC





0	linux.master.ad3081b4f8	(A)	-	+
0	now		*	+

Limit results to 0 rows (0 for unlimited)

Apply Clear Create Hyperlink

· · · · · · · · ·		
Contin	HOUSE	

iite	Build Name	Update	Con	figure	В	uild		Test			
ne	Build Hallie	Files	Error	Warn	Error	Warn	Not Run	Fail	Pass	Build Time	Labels
ip-172-31-25-119	master_vicon_ground_truth/873.linux.master.ad3081b4f8	0	0	0	0	2	0	0	205	1 hour ago	(132 labels)








Computational Model Builder and The Reactor Geometry

Generator Projects


Builder



Goals:

- Develop an application framework that can be easily adapted to specific problem domains
 - Geometric Domain and Assembly Model Creation
 - Simulation Creation
 - Simulation Execution
- Quickly create custom applications/workflows
- Leverage existing and future simulators, meshers, and toolkits
- Develop a simulation model toolkit (SMTK) analogous to VTK for supporting simulation models
- All development under BSD licensing





Libraries Used in CMB

- SMTK
- VTK
- ParaView
- QT
- VXL
- MOAB
- CGM
- OpenCascade
- Boost
- ReMUs
- ZeroMQ


- Shiboken
- Lasso
- HDF5
- NetCDF
- Zlib
- PNG
- Szip
- Pugi XML
- MPI
- Gdal
- Ftgl




Reactor Geometry Generator (RGG) Goals:


- Provide a set of easy to use model and mesh generation components/applications that support various Nuclear Energy Workflows
- Support Client/Server Framework as well as HPC Environments
- Leverage existing efforts being developed within the DOE





Model of a Sodium Cooled Fast Reactor Core Modeled & Meshed in RGG






Libraries Used in RGG

- VTK
- QT
- MOAB
- CGM
- OpenCascade
- Boost
- ReMUs
- ZeroMQ
- CUBIT

- Lasso
- HDF5
- NetCDF
- Zlib
- PNG
- Szip
- MPI
- Ftgl



Virtual Pediatric Airways Workbench (VPAW)



VPAW is a surgical planning system for pediatric upper airway obstructions


3D interactive editing of airway geometry with 3D input devices to explore possible surgical outcomes

Dependencies built with CMake:

- VTK
- ITK
- VRPN
- quatlib
- jsoncpp
- CLAPACK



Case study



ARC Centre of Excellence for Autonomous Systems- Australia



The Argo is fully automated with the onboard computers all using code built using CMake. The Helicopter is semi-automated with the pilot following a course determined by the onboard computers interacting with the Argo. Everything uses CMake, QNX dashboard
















ParaView

ParaView is an open-source, multi-platform, data analysis and visualization application for analyzing extremely large datasets using distributed memory computing resources.












open-source








A CONTRACTOR OF THE PARTY OF TH	Previous Current Hest Projec														
io file changed as of Saturday, May 16 20	15 - 20:00 EDT														Q
HPC Sites	with the same of t	-	Jodote	-	Conf		-	9.	100	_		Test		-	
te .	Build Name		Time	Torre .	Warn	10/10/2	-	Warn		Not Bun	Fell	Pass	Time	Build Time	Lab
ANY ATI	∆ Tukey-righty-exet	0	1100	n B	oram	Dm 36s	0		71n 6%	PACK PRAIN	Pan	Pass	Time.	23 hours ago	o proc
master	The state of the s										No.			Contract sign	-
(September 1997)		1	Lipdate		Corr	fgure		- B	ald		0.7	Test	117		П
10	Build Name	Files	Time	Kerne	Ware	Time	Errer	Warn	Tree	Not Fun	Fall	Pass	Time	Build Time	Lab
moet	605242e6-build 165 garaview-amber8-linux-static- relosse-covressa				0	217 18s	0	e	31m 12s	0		38	tmes	11 hours ago	nor
moed	5 6:0024246 - oulict05-paraview-amber3-linux-static- release+mpi+pamesa+python			0	0	4rt 20s	0	0	49m 24a	0		108	2m 34s	10 hours ago	no
ignac	E RXEDIZINE-build186-paraview-bigmac-csix-shared- bibug-blang-python			0	0	24	0	0	21m 48e	0		10	60a	11 hours ago	inor
ernesis	Bc824248-cu3d016-paraview-nemesis-aincows-shared- release+gui-kife+mpi+python	0		04 0	0	4m 5s	0	1	33m 42s	9		530	15m 48s	10 hours ago	ro
ervation	BIOS24246-DUIGS21-paraview-tarvason-windows-shared- release-gui-mpi-vs	a		16n B	u	1011 42s	ú		10:47m 18s	ä		457	18m 12s	11 hours ago	no
rerande	8d5242e6-build227-peraview-mrande-wndows-shared- release+30txt+gui	0		125 0	0	žn 42s	0		31m 36s			423	11m Ma	# hours ago	ro
arvalon	8x824246-bulic223-paraview-bavaron-windows-static- resease-gua-reprive	0	3	16- 0	0	1011186	0		2h 34m 54s	0		453	17m 48h	9 hours ago	ro
ney.	6x6242x6-bulk(233-paraview-trey-osa-static- release-gui-kits-python	0		0- 0	0	2m 12a	0		56m 18a	0		525	2101425	\$ hours ago	ro




data analysis & vis





data analysis & vis





dependencies

	Linux 64 bit	Windows 64 bit	Windows 32 bit	Mac OS X 64 bit				
ParaView		GIT Tag v	4.4.0					
Compiler	GCC 4.2.1 with libc 2.3.6	Visual Studio 2008 x64 9.0.30729.1 SP	Visual Studio 2008 x86 9.0.30729.1 SP	10.7 SDK under Xcode 4.3				
Build Platform	Debian GNU/Linux 4.0r9, amd64	Windows 7 Ultimate, Service Pack 1, 64-bit	Windows 7 Ultimate, Service Pack 1, 64-bit	OSX 10.7.3 64-bit				
zlib		v 1.2.7	7					
libpng		v 1.4.8	}					
freetype		v 2.4.8	}					
fontconfig	v 2.8.0 -na-							
szip		v 2.1						
hdf5	v 1.8.13							
silo	v 4.9.1							
cgns		v 3.1.3-	4					
ffmpeg	v 2.3.3 -na- v 2.3.3							
libxml2		v 2.7.8	3					
Qt		v 4.8.6	3					
Python	v 2.7.2	v 2	7.3	v 2.7.1				
NumPy		v 1.6.2	2					
matplotlib		v 1.1.1						
Boost		v 1.56.	0					
MPI	MPICH2, v 1.4.1p1	OpenMP	I, v 1.4.4	MPICH2, v 1.4.1p1				
Manta	r2439	-n	a-	r2439				



highlights


- ~60K lines of CMake code (excluding ~160K lines of CMake code from VTK)
- Uses superbuild for building dependencies, generating redistributable packages, and cross compiling.
- Broad set of dependencies: Qt, Python (NumPy, Matplotlib), Boost, MPI, CGNS, HDF5, fontconfig etc.
- Multi-platform building and packaging with CMake/CPack: OsX, Linux, Windows
- Cross compile support:
 - BlueGene Q (Mira: Argonne Leadership Computing Facility)
 - Cray XK7 (Titan: Oak Ridge Leadership Computing Facility)




Example: 3DSlicer

An open-source platform for delivering image analysis technology for personalized medicine research.




















The Slicer Ecosystem



- Major building blocks:
 VTK, ITK, CTK, Qt, Python,
 Teem, PythonQt, ...
- Key infrastructure:
 CMake, CTest, CDash,
 MediaWiki, GitHub....
 - Distribution mechanisms:
 Extension manager for software distribution, data store for data distribution
 - Slicer for end-users



Packages used by Slicer


 CTKAPPLAUNCHER, CTK, CTKResEdit, curl, DCMTK, incrTcl, ITKv4, LibArchive, NUMPY, OpenIGTLink, OpenSSL, PCRE, python-async, python-chardet, python, python-gitdb, python-GitPython, python-nose, python-pydicom, python-PyGithub, python-setuptools, pythonsmmap, qRestAPI, Qt4, SimpleITK, SlicerExecutionModel, Swig, tcl, teem, tk, VTKv6, zlib




Examples of Clinical Projects

Radiation dose calculations


Tracking peritumoral white matter fibers





Prostate procedures

Diagnosis of **Different Tumors** in Lung Cancer




Clinical users drive creation of technology



Breast cancer surgery guidance

Model-Guided Deep **Brain Simulation**





Diagnosis of Osteoarthritis Degeneration

Quantitative assessment of COPD

navigation





SonoVol A: "Case Study"

- SonoVol is a spinout from UNC Chapel Hill's Joint Department of Biomedical Engineering.
- Grad student and professor designed some robotic hardware for improved preclinical ultrasound imaging
- Needed a software interface for controlling hardware, and viewing image data.








Paul Dayton





- Improved "MRI-like" field of view
- Ability to study anatomical context of tumors over time
- High throughput acquisitions
- Multi-modality registration
- Improved blood vessel quantification







CMake, CTest, and CDash at Netflix

Posted in CMake. Viewed 5489 times.



At the Core Technologies team at Netflix, we develop the application framework and streaming engine used by millions of consumer electronics devices, game consoles, tablets, and phones. With such a diverse array of devices and platforms, we need to make sure our code is lightweight, standards compliant, and portable. As we also produce the SDK that is used by partners to port Netflix to their devices, we need to make sure that it builds and runs well across many versions of

the C++ compiler and standard C libraries.


We found that CMake was the tool that better fit our needs: It created project files for all development environments we used, was easily extensible with its own scripting language, provided cross-platform commands to copy and delete files and directories, and was easy to deploy on our Jenkins nodes.

	Learny natifice commission of the controlled gray for each in NACAPT & LT 46, have	+714 \$ 12 mg								Citter too	
n innym ty hadron ar a' Namako.	NAME OF STREET							Special	innibat Paralit, Laren	THE THE RESERVE AND THE PARTY NAMED IN	
	horizo	100		Territoria de la compansión de la compan			lancour of the lancour	. Date.		6000	
med	Danner 1	- No.	Dist	-	610		bolo	-	1000	\$4.00 KIND	
med	Tanner I	100000	1000	10000			-		10000	Decide Selection of the Control	
Tani	Tanner 1	1.00			-				100	Star M. Alley Holland	
wast.	Tanaca -	10000	1000	1000000	(40)			- 0	100	Section of the least	
r Proporti	August v	100.00				-		- 50-	10000	Section 2015 in accord	
MARK .	3 among r	1000		1000	80	100.00		100	10000	Section of the last	
med .	A sensor to		100		90			- 20	100	Decide proc. proc. mol. mol.	
remail .	Same of the same o	11 (X)		100	100	10000		200	1000	No. 10. ACCUPATE	
West	3 some o	100			A01			- 20	1000	the Rolling of Artist	
Massi	Suppose 1	100		200	- 60			36	1000	No. 8, 211 (EURY)	
M-607	A season v	N			100					Section and the	
resad	Tames C	100		10000	- 55			- 24	10007	See 4. Set. School	
Marie Control	Remove 1	100							100	See 18, 2011, 30-27507	
read.	A service of the Control of the Cont	100		10.500	-	100		-		NAME AND ADDRESS OF THE PARTY.	
The section of the se	3 annual C	100	- 10	100	-		100			No. 80, 510 (1970)	
The state of the s	A service of	1100000	- 00		-0.0			- 6 -	100	The R. Str. Science	
erest.	Change of	100000			100			0.00	12 (2)	NAME OF PERSONS	
The state of the s	Tables 1	1000						- 2	100000	Name of Associated	
Head	Dames o	10000	1340	974000	1			200	10000	Decid Strik Steal Poli	
the state of the s	Same v	1000			- 60				1000	Decide and or party.	
_										The second second	
to.	No.	10.25	Sec. Sec.	92	-	· Comment		- ter		Solida	
manus de la companya	A processor late, Monte, Parings, 7	100	THE REAL PROPERTY.			-	Ar he	-	Ten.	06 8 AV. 1/8 TO	
earlest.	A second We have forms ?	Total Control	-	100000		_			100	Section Section	
earned.	A second part and the second	100			_	- 1		_	_	THE REST ASSESSED.	
Automatic Committee Commit	The assessment of the section of the	100/4200	-				_	_	-	De M. Mrs. (018-76)	
manus.	3 months had with not just to								THE RESERVE	Section and the section of	
meter)	T character Mt Monte, Barrie, 1		-		_		ALC: UNKNOWN			Decision worker	
manust.	A common the many troops I	100		10000		_			1	facility and of sector	
THE											
stead do	name of the base of			_	_	riti bass,,	_	-15 mm		No. of Street	
read .	satisfied of					NAME AND DESCRIPTION OF THE PERSON NAMED IN COLUMN NAMED IN CO				Design the second	
Their	sales at			ent.	_	417		811		Della Still Harrist	
read	400.0					milit .		-		Decide and recognition	
re-and	2000 C		8150					200		Section Control	
Marie Company	same at			e inc		MON.		3148		Section to select	
Transi	activité al			E36%		600.		400		Name and Address of the Owner, where the	
Property.	ARREST AT			epite .		401		No.		Deck by work	
resent.	4690.9			KIRK .		8679		(600)		Sec. M. Strick Strick Party	
Head	NAME OF			100		400		been.		DURATE WHITE	
The second	anne di			CHO.		404		No.		THE REST CONTRACT	
their .	anni d			CON.		404		-		184 R PO 185 PT	
read	and a			40	_	400		-		No. 2 and 10 days	
rhadi .					_	404		-		(No. 80, 2010 - 2010 PG)	
18 auf	Miles at					414		-		Secretary and the secretary	
Page 1	same of			ein.		800		-		Switch Street, Spiritely	
mad	sales of			distr.		mbe:		town.		Section and displayer	
Make 1	6440-E		-	nijelia.		ecim		0.00		San-Strates, weighted	
Maid	MAN W			KINN .		400		(many		NUMBER WATER	
read	select of			elm:		#1(B		(0.00)		040,000,000	
eared.	CHARGE (M. Street, Street,)			elec		3000		980		INCRESS STREET	
naned .	(Payment Ph., Novie, Novies, 7			CHP.		910		(mate)		Ger R. Stille JH, St. Ph.	
against S	alestec (B) (book, book,)			OMS.		200		(MARK)		\$60.00 (00.000)	
THE RESERVE OF THE PERSON NAMED IN COLUMN TWO IS NOT THE PERSON NAMED IN COLUMN TWO IS NAME	displacinity (Bursa) (Bridge).		- 10	(9)	_	316		1140	_	Design and Artistics	
anti Arabah	Borbon .		_		Total Control		_	-			
****	should figure the later				reigner .					THE R. P. LEWIS CO., LANSING	
	stream rigg, sam, sat, jame stream rigg, sam, sat, sam.										



Kitware Computer Vision

Object and Building Recognition by Function (DARPA)





KWIVER Toolkit

Kitware Image and Video Exploitation and Retrieval Toolkit


An Open Source, production-quality video exploitation system


- Engage the community: academic, industry, government
- Avoid expensive software duplication and redundancy, speed time to solution
- Leverage the "many eyes" of the community to improve quality, stability and utility
- Bridge the gaps between research code → production software, initial feasibility
 → operational evaluation
- Create a true open-source community for cooperative, distributed development based upon available Open Source toolkits
- Scale down to a single researcher's desktop and up to multi-node clusters



A KWIVER Enabled System










Fletch – A Computer Vision Tool Chest







MAP-Tk

Motion-imagery Aerial Photogrammetry Toolkit

- Open source with permissive BSD license https://github.com/kitware/maptk
- Highly modular, open framework
- OpenCL (GPU) accelerated feature detector and descriptor option.
- Optimized for aerial video processing
 - Frame-to-frame homography guided feature tracking
 - Homography guided loop-closure
- Recovery from bad frames during tracking
- Temporally hierarchical bundle adjustment
- Estimate shared, but unknown, intrinsics







15 Years of CMake

 CMake just had a birthday and is 15, over that decade and a half it has had a huge impact on scientific efforts involving C/C++





Building Science with CMake

- Reproducible builds across multiple platforms
- Integration with CI testing tools
- Integration with Data tools allowing for algorithm testing as well as unit testing
- Many domains: Medical imaging, Computer
 Vision, Robotics, Nuclear Energy, many others
- Open Source enabling use by many collaborators



Thanks

Build, Test & Package

- Many users and contributors of CMake
- Awesome developers at Kitware
- Google and the Google Tango Project

